

Name: _____

Student ID #: _____

Lab #4: COMP 3000B (Operating Systems)
March 13, 2007

Please answer all questions below, there are 60 marks total. Part A of this lab is intended to be completed within the lab during Lab hours. Part B can be completed on your own time, either in the lab or on your own computer.

You may find the Linux Cross Reference website, <http://lxr.linux.no/source/>, useful when completing this assignment.

1 Part A

This section is designed to be completed in the lab. You get 10% of the total marks for attempting to do part A during assigned lab hours. Please ensure that one of the Lab instructors takes your attendance.

1. [6] Have the instructor mark down that you were present and attempted part A during lab hours.
2. [3] In the Linux kernel, what file contains the code for the system call dispatcher that executes on the machines in the lab? What language is it written in? Why?
3. [2] What is the highest numbered system call currently implemented? What is the name of this system call?
4. [2] Look in the file `linux-2.6.19.1/fs/ext3/file.c`. What function implements the read operation for ext3 filesystems? The write function? (Note that one is filesystem specific, while the other is generic.)
5. [2] In what file are the directory inode operations of ext3 defined? In what structure?
6. [3] What function (from what file) calls `do_execve()` on the kernels running in the lab? Why can't the system call dispatcher directly call `do_execve()`?
7. [2] Briefly, what is the purpose of the `bprm` structure as used in the function `do_execve()`?

2 Part B

The kernel source on the lab computers contains a skeleton file which will be used in completing this lab. This file is located at `kernel/comp3000.c`. Currently, the code in the file creates a proc filesystem entry at `/proc/comp3000` that outputs *Hello World*. In this lab, you will be modifying the file `comp3000` to do more.

While you do not need to turn in the entire `comp3000.c` source file, please do give enough context so it is clear where you made your modifications.

1. **[10]** Modify `kernel/comp3000.c` to output the process number and name of the process which has a PID closest to 1000 (without going over).
2. **[20]** Modify `kernel/comp3000.c` to output a complete list of process ID and command lines. Your output should be similar to that seen when running the `ps -e --format "pid args"`.
3. **[10]** Modify `kernel/comp3000.c` so that you can write a number to the proc filesystem and subsequent reads will return all processes with ID's above the number written. Writing an ID number of 0 should result in all processes being shown when reading from the proc file.